Ⅲ Mohawk Group

Hot and Heavy Collection



DESIGN

Product Type: Floating LVT Overall Thickness: 5 mm (.2") 20 mil (0.5 mm) Wear Layer: M-Force Ultra Finish:

Surface Profile: Wood Emboss; Light Emboss

Edge Profile: Bevel

235mm x 1505mm (actual) 9"W x 59"L (nominal)

22.84 sf/ctn (2.12 m²/ctn)

Pieces Per Carton: 6 pieces/ctn

Pounds Per Carton: 40.78 lbs/ctn (18.49 kg/ctn)

Installation Method: Loose Lay with Perimeter Glue or Full Spread M95.0 Resilient Flooring Adhesive, M99 Resilient Flooring Adhesive, or M700 Adhesive Recommended Adhesive:

SUSTAINABILITY

Certification: FloorScore® certified

Pre Consumer RC: 37% Post Consumer RC: 22%

PERFORMANCE

Construction: Commercial Grade Loose Lay Luxury Vinyl Tile Classification: ASTM F1700 - Class III, Type A - Smooth, Type B -

Squareness: ASTM 2421/ASTM F2055 - Passes - ± 0.10 in. max

Size And Tolerance: ASTM 2421/ASTM F2055 - Passes - ± 0.016 in. per linear foot

Thickness: ASTM F386 - Passes - as specified ±0.005 in.

Flexibility: ASTM F137 - Passes - 1" mandrel

Dimensional Stability: ASTM F2199 - Passes - 0.020 in. per linear foot Static Load: ASTM F970 - Passes, modified - 1000 psi

ASTM F1914 - Passes - Average less than 8%, Residual Indentation:

maximum single read 10%

Resistance To Chemicals: ASTM F925 - Passes - No Change or Slight Change

ASTM F1515 - Passes - $\Delta E \le 8$ Resistance To Light: Resistance To Heat: ASTM F1514 - Passes - $\Delta E \le 8$

ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1 Critical Radiant Flux:

Smoke Density: ASTME662 - Part A - less than 450

SERVICE

Limited 20 Year M-Force Ultra Commercial Warranty Warranties:

352

Sierra

Quickship Available

148

Atwell Mill

Quickship Available



Arrowhead Creek

Quickship Available

123

Benmore Quickship Available

833 Quickship Available



333

Redwood

Quickship Available

Kew Gardens

Quickship Available

Picton Park Quickship Available



878 Woodland Quickship Available

Hot and Heavy Collection









