



WATERFORD 9"

FEATURES

Realistic Wood Visuals precisely mimic wood look and texture.

Solid Core Construction is made of extruded stone instead of thermoplastics for maximum strength and dimensional stability.

Resists Scuffs and Abrasion using UV Cured Urethane Aluminum Oxide finish with microscopic particles to protect the surface from premature wear.

SPECIFICATIONS

Plank Size	6.5 mm x 9" x 60"
Thickness	6.5 mm (5 mm + 1.5 mm Underlayment)
Core	Extruded Stone
Visual	Wood Embossed
Color Variation	Low-Medium
Edge Profile	Micro Bevel
Wear Layer	22 mil (0.55 mm)
Finish Gloss Level	Urethane Aluminum Oxide Matte
Installation Method	Float Licensed Locking
Installation Levels	Any Grade Level
Radiant Heat Approved?	Yes (infloor hydronic)
Virgin PVC	Yes
Certifications	FloorScore™ Phthalate Free
WARRANTIES	PSI Passes ASTM F970
35 Year	Limited Residential
12 Year	Limited Commercial
CARTON CONFIGURATION	
Pcs/Carton	6 48.71 lbs/carton

Packaging

6 | 48.71 lbs/carton 32.53 sq. ft./carton | 52 cartons/pallet

TRIM OPTIONS

End Cap T-Mold Reducer Stair Nose

SEE REVERSE SIDE FOR MOLDING INFORMATION



For more information visit naturallyagedflooring.com or call Toll Free (800)245–0652

WATERFORD9"



FLOOR CARE AND MAINTENANCE

- To clean, regularly sweep or vacuum, along with periodic use of an approved no-wax hardwood floor cleaner.
- Clean up spills promptly with a soft cloth and recommended products.
- Place felt-type protectors on the bottom of all furniture and fixture legs to assist in preventing denting and scratching.
- To prevent scratches and dents, avoid wearing spiked shoes (such as sports cleats) on flooring.
- The exposure of sun, UV rays, and artificial lighting can cause the wood and/or stain to change color and/or fade over time.
- For more details, refer to Floor Care and Preventative Maintenance on harrisflooring.com.



For more information visit naturallyagedflooring.com or call Toll Free (800)245-0652